



NOTES: UNLESS OTHERWISE SPECIFIED:

- 1 PADS TO BE GOLD PLATED
- 2 VIAS IN PAD AREAS MUST BE FILLED

© COPYRIGHT 2024 TEXAS INSTRUMENTS  
UNPUBLISHED, ALL RIGHTS RESERVED

REVISIONS			
REV	DESCRIPTION	DATE	BY
A	INITIAL RELEASE	10/16/2024	JTM

4X Ø3.600±0.050  
⊕ 0.300 A B C

0.25 A B C

2.556  
2X 4.150

7.57

13.88

2X 17.850  
(18.146)

22.000±0.070

(28.50)

(13.00)

2X 8.500

PAD M22

(4.0832)

2.58

0.000±0.070

Ø2.400±0.040

1.84

4.0832

PAD A20

2X 8.500

(13.00)

149X LGA PADS  
0.52±0.03 X 0.52±0.03

⊕ 0.100 A B C

21X 0.7424= 15.5904

(35.000)

A

1.400±0.140

UNLESS OTHERWISE SPECIFIED

- DIMENSIONS ARE IN MILLIMETERS
- TOLERANCES: ANGLES ±1°  
2 PLACE DECIMALS ±0.25  
1 PLACE DECIMALS ±0.50
- DIMENSIONAL LIMITS APPLY BEFORE PROCESSES
- INTERPRET DIMENSIONS IN ACCORDANCE WITH ASME Y14.5M-1994
- REMOVE ALL BURRS AND SHARP EDGES
- PARENTHETICAL INFO FOR REF ONLY

DWN J. McKINLEY	DATE
Engr	
CQE/QA	
CM	
Apprvd	



PCB, DMD ASSEMBLY, OUTLINE,  
SERIES 323

SIZE	DWG NO	REV
B	2519248	A
SCALE 2:1		SHEET 1 OF 2

