

LMX9838 DONGLE Hardware User Guide

Texas Instruments
Application Note 1710
Markus Roemer
September 2007
Updated February 2013



1.0 Scope

Texas Instruments LMX9838 Bluetooth™ serial dongle evaluation kit is a plug and play serial adapter for serial cable replacement applications and more. It is able to support more profiles than just the Serial Port Profile (including audio support with external codec boards). By using the enclosed Simply Blue Commander software, it allows user to develop their own SW applications easily given the built in interpreter for HEX commands. SBSmart is a higher level application tool that provides buttons with the built in commands to easily set up or demonstrate different profile support using the Simply Blue SPP package.

2.0 General Description

2.1 EVALUATION KIT CONTENTS

- LMX9838 Bluetooth serial adapter reference board
- USB Dongle and application software stack
- Null modem cable
- 110V to 240V AC to 5V DC power adapter and pigtail
- CDROM with design documents and Simply Blue software Application tools.

2.2 LMX9838 BLUETOOTH SERIAL ADAPTER




Figure 1. LMX9838Dongle

3.0 Qualification

- FCC certified:
 - FCC ID: ED9LMX9838
- FCC compliance: The device complies with Part 15 of FCC Rules. Operation is subject to the following two conditions:
 - IC certified:
 - IC: 1520A-LMX9838
 - Bluetooth SIG QD ID: B012394

4.0 Requirement and Setup

4.1 BASIC REQUIREMENT

- X86 PC with serial port.
- One of the following operating system is required.
 - Windows XP
 - Windows 7

4.2 APPLICATION SOFTWARE

4.2.1 Simply Blue Commander

Application command oriented tool to generate commands and watch events in the Simply Blue Command interface window. Reference the Simply Blue Commander User Guide document for details.

4.2.2 SBSmart

Easy to use Windows based tool to demonstrate additional profile support of the Simply Blue functionality. Reference the SBSmart User Guide for additional details.

4.2.3 Patch Programming

LMX9838 allows for patch programming for firmware updates if necessary. Reference [2] for details. This can also be done with the Simply Blue Commander and SBSmart tools.




Figure 2. System Block Diagram

5.0 Functional Description

5.1 POWER SUPPLY

- DC Power Jack (6V max)
- Battery Holder (6V max)

5.2 MAIN SYSTEM

- Reset button for manual Reset
- Jumper option for Baud rate selection

5.3 UART INTERFACE

DB9 connector for RS232 standard PC interface using On-board level shifter IC for handling LMX9838 module's 3.3V UART interface.

5.4 ADVANCE AUDIO INTERFACE

- Support Audio applications
- PCM codec interface (support linear and A-law)
- PCM Master or Slave operation (SW configurable)

6.0 Design Consideration

6.1 POWER MANAGEMENT

- 3.3V output single LDO is used to provide power for RS232 interface chip and Digital portion of the LMX9838.

7.0 Layout

The LMX9838 reference design is split into 2 sections, one section is RS232 transceiver circuit for PC connection, another section is LMX9838 main circuit for Host processor.

7.1 PCB DESIGN

- 4 layers PCB
- 1.6 mm overall thickness

7.2 LAYERS CLASSIFICATION

- Top layer is the components and connection wiring
- Layer 2 is Ground plane
- Layer 3 is Power plane
- Bottom layer is interface signals




Figure 3. LMX9838Dongle

8.0 Board components and Pin Assignments

A summary of the configuration and selection jumpers is provided in the tables that follow. Reference both the schematic and PCB layout (included on the CD in the kit)

Table 1. Major Components List

Device	Description
U1	TI LMX9838 Serial Port Module - Reference the device datasheet.
U3	TI LP3985 Low-Dropout Voltage Regulator
U2	Maxim MAX3225 1 Mbps High Speed UART Driver

Table 2 Connectors Summary

Connector	Description	Details
J7	Battery Connector 2mm pitch	Maximum input voltage is 6V
J6	DC jack	Same as above
J8	DP9 serial connector (male)	See Table 5
J5	External processor interface	See Table 6
J4	Advance Audio interface	See Table 7

Table 3 Jumper and Test Point Summary

Jumper / Test Point	Description	Details
J1, J2 and J3	Clock & UART setting jumper	See Table 8

Table 4 Switch and LEDs

Switch/LED	Description
S1	Reset button
D1	Operation Status
D2	Data Traffic (TX/RX)

Table 5 J8 DP9 (male) Pin Assignments

Pin #	Signal name	Description
1	NC	No connection
2	RxD	Receive Data (input)
3	TxD	Transmit Data (output)
4	NC	No connection
5	GND	Ground
6	NC	No connection
7	RTS	Ready to send (output)
8	CTS	Clear to send (input)
9	NC	No connection

Table 6 J5 External Processor Interface

Pin #	Signal name	Description
1	NC	No connection
2	VCC	LDO output (3.3V)
3	GND	Ground
4	TXD	Transmit Data (output)
5	CTS#	Clear to send (input)
6	RXD	Receive Data (input)
7	RTS#	Ready to send (output)
8	VCC_CORE_IN	1.8V voltage regulator input/output
9	RESET#	Reset (input)

Table 7 J4 Advance Audio Interface

Pin #	Signal name	Description
1	VCC	LDO output (3.3V)
2	SCLK	Advanced Audio Interface Clock
3	STD	Advanced Audio Interface Transmit Data
4	SFS	Advanced Audio Interface Frame Synchronization
5	SRD	Advanced Audio Interface Receive Data
6	GND	Ground

Table 8 UART interface setting

J2	J3	J1	UART baud rate
Short	Short	Short	921600bps
Short	Open	Short	115200bps(default)
Open	Short	Short	9600bps
Open	Open	Short	NVS (Default 9600bps)

9.0 Bill of Materials

Item Name	Description	Vendor	Part Number
C5,C6	Capacitor 22p 0603 C0G 50V	MuRata	GRM39C0G220J50
C1,C3,C8, C10	Capacitor 100n 0603 Y5V 50V	MuRata	GRM39Y5V104Z50
C2,C4,C7	Capacitor 2u2F 0603 Y5V 10V	MuRata	GRM39Y5V225Z10
C9	Capacitor 100p 0603 C0G 50V	MuRata	GRM39C0G101J50
C11,C12	TANT CAP 1uF 16V SIZE A	Any	
C13,C14,C15 ,C16,C17	Capacitor 1uF 1206 X7R 25V	MuRata	GRM42-6X7R105K25
C19	Capacitor 1uF 0603 Y5V 10V	MuRata	GRM39Y5V105Z10
J7	Battery holder (2mm pitch)	Any	
S1	TACK SWITCH TS-1135HS	RAINBOW	
Y1	Tuning fork crystal 32.768KHz	Any	
J6	DC POWER JACK	Morning star limited	DC-015
D1	Red Color LED 0603 Size	Any	
D2	Blue Color LED 0603 Size	Any	
J8	DB9 (male) serial connector	Any	
J4	2mm Socket (6 poles)	Any	
U1	Bluetooth SPP Micro Module	Texas Instruments	LMX9838SB
U3	Low Dropout Regulator	Texas Instruments	LP3985IM5X-3.3
U2	High Speed RS232 Transceivers	Maxim	MAX3225EEAP+
R1,R2,R3	Resistor 0603 Size, 1K	Any	
R11,R12	Resistor 0603 Size, 10K	Any	
R6,R7,R8,R9, R13,R14,R17	Resistor 0603 Size, 0R	Any	
R4,R5	Resistor 0603 Size, 330R	Any	
J3,J10	2mm header	Any	
J1,J2	2mm header (with jumper)	Any	

100 Bibliography

- [1] LMX9838 Bluetooth Serial Port Module data sheet
- [2] AN1699-LMX9838 Bluetooth Serial Port Module - Software Users Guide
- [3] SBSmart user guide

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Applications Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Automotive and Transportation	www.ti.com/automotive
Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Video and Imaging	www.ti.com/video

TI E2E Community

e2e.ti.com